



尺寸

产品名称	A	B	C	D	(G)	H	(M)	订单编号
GPN 330 L10	16	6.4	10.5	4.4	5.5	4.1	26.5	330 0010 0000
GPN 330 L12	14.3	6.4	12.3	4.4	5.5	4.1	26.5	330 0012 0000
GPN 330 L14	16.3	8.4	14.3	6.4	5.5	4.1	26.5	330 0014 0000
GPN 330 L16	18.3	10.4	16.3	8.4	5.5	4.1	26.5	330 0016 0000
GPN 330 L18	21	10.4	18.5	8.4	5.5	4.1	26.5	330 0018 0000
GPN 330 L19	21	13.6	19.7	11.6	8.3	6.1	29.3	330 0019 0000
GPN 330 L20	22.5	13.6	20.7	11.6	8.3	6.1	29.3	330 0020 0000
GPN 330 L22	25	16.4	22.9	14.4	8.3	7.6	29.3	330 0022 0000
GPN 330 L24	27	16.4	24.9	14.4	8.3	7.6	29.3	330 0024 0000
GPN 330 L27	30	19.6	27.9	17.6	8.3	8.1	29.3	330 0027 0000
GPN 330 L28	31	19.6	28.8	17.6	8.3	7.9	29.3	330 0028 0000
GPN 330 L39	46	26.2	39.5	24.2	11.4	11	32.4	330 0039 0000

尺寸单位: 毫米

产品材料、颜色、图纸和用途信息, 请参阅第 124/125 页。

标准色: 黄色

材料: PE-LD



## 节省时间。

实用拉环设计, 便于拆除。



## 更多用途。

柔性轴凸筋, 可适应更大公差。



## 更优质。

适用于钻孔和内螺纹。也可用于带联管螺母的特殊管件。凸筋接合至螺纹并将联管螺母定位于导体末端。

\* 本应用表仅作参考之用。我们乐意为您寄送免费样品进行测试。不带螺纹的孔隙和钻孔, 请使用尺寸B和C。

您还可能对下列产品感兴趣: GPN 305, GPN 308, GPN 310, GPN 615

## 应用指南\*

## 公制螺纹

标准螺纹	细牙螺纹	管螺纹	产品名称
M 10 × 1		1/8	GPN 330 L 12
M 12	M 12 × 1	1/4	GPN 330 L 12
M 14	M 14 × 1	1/4	GPN 330 L 14
M 16	M 16 × 1	3/8	GPN 330 L 16
M 18	M 18 × 1	3/8	GPN 330 L 18
M 18	M 18 × 1	1/2	GPN 330 L 18
M 20	M 20 × 1	1/2	GPN 330 L 19
M 20	M 20 × 1	5/8	GPN 330 L 20
M 24	M 22 × 1	5/8	GPN 330 L 22
M 24	M 24 × 1		GPN 330 L 24
M 24	M 25 × 1		GPN 330 L 24
M 27	M 26 × 1	3/4	GPN 330 L 27
M 27	M 27 × 1		GPN 330 L 27
M 27	M 27 × 1	7/8	GPN 330 L 28
M 30	M 28 × 1		GPN 330 L 28
M 30	M 29 × 1		GPN 330 L 28
M 39	M 34 × 1		GPN 330 L 39
M 39	M 35 × 1		GPN 330 L 39
M 39	M 36 × 1		GPN 330 L 39
M 39	M 37 × 1		GPN 330 L 39
	M 38 × 1.5		GPN 330 L 39